

# Compact workgroup productivity.

imageRUNNER  
2520/i, 2525/i, 2530/i,  
2535/i, 2545/i

**you can**

A RANGE OF SPEEDS FROM 20 TO 45 PPM / CPM, A3 BLACK-AND-WHITE

UP TO 2,300 SHEET PAPER CAPACITY

SEND DIRECT TO EMAIL AND NETWORK FOLDER

5.7 INCH / 14.47 CM TOUCH SCREEN DISPLAY

CLASS-LEADING ENERGY EFFICIENCY

COMPACT DESIGN

Ideal for busy, small and medium workgroups, this versatile range provides for everyday black-and-white printing, copying, colour scanning and advanced send direct to email and network folder. With a variety of speeds up to 45 ppm, excellent responsiveness and energy efficiency these devices will save you time, money and energy.



## Productivity and efficiency

- Easy-to-use touch-screen display saves time
- Fast output speeds up to 45 ppm
- Send in colour to network folders or email in a variety of formats\*
- Fewer interruptions with up to 2,300 sheet paper capacity
- Simple, hassle-free integration – Network ready, PCL\* and optional PostScript Support
- Optional inner staple finisher
- e-Maintenance service provides remote diagnostics, automated meter readings and toner management.

## Environmental

- Exceptional energy efficiency – as little as 1.5 watts power consumption in sleep mode, saves energy and cost
- Save paper – automatic double-sided output.

## Cost-effective

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance.

## Security

- Secure Print\*\* keeps documents confidential during printing
- Department ID secures access to the device
- uniFLOW compatibility offers the flexibility and convenience of My Print Anywhere secure release with job selection.

\* Standard on i models, optional on non i models  
\*\* RAM-based secure print for up to 100 jobs

imageRUNNER

**Canon**

# Specifications: imageRUNNER 2500 Series

Type	Desktop or Free-standing (Reader-Printer Combined)	
Maximum Original Size	A3	
Copy Sizes	Cassette 1, 3, 4 A3, A4, A4R, A5R. Custom size: 139.7 to 297mm x 182 to 432mm	
	Cassette 2	A3, A4, A4R, A5R
	Stack Bypass	A3, A4, A4R, A5R
	Custom Size	99 to 297mm x 148 to 432mm
Resolution	Reading	600dpi x 600dpi
	Copying	600dpi x 600dpi
	Printing	600dpi x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
	No. of Tones	256 Gradations
<b>COPY/PRINT SPEED</b>		
	A4	imageRUNNER 2545i / 2545: 45ppm (BW) imageRUNNER 2535i / 2535: 35ppm (BW) imageRUNNER 2530i / 2530: 30ppm (BW) imageRUNNER 2520i / 2520: 25ppm (BW) imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 22ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW) imageRUNNER 2520i / 2520: 15ppm (BW)
	A3	imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 15ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW)
	Magnification	25-400%; Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400%
	First Copy Time	3.9 sec (45 / 35ppm model), 5.4 sec (30 / 25ppm model), 6.4 sec (20ppm model)
	Black & White	30 seconds
	Warm-Up Time	1 to 999 sheets
	Multiple Copies/Prints	Duplexing Standard
	Duplexing	Standard
	Paper Weight	Cassette 64 to 90g/m <sup>2</sup> ; Stack Bypass: 64 to 128g/m <sup>2</sup> ; Duplex: 64 to 80g/m <sup>2</sup>
	Paper Capacity	Cassette 1 550 sheets (80g/m <sup>2</sup> ) (250 sheets for the imageRUNNER 2520i / 2520) Cassette 2 550 sheets for imageRUNNER 2525i, 2530i/i, 2535i/i, 2545i/i Stack Bypass 100 sheets (A4, A4R, A5; 80g/m <sup>2</sup> ), 50 sheets (A3; 80g/m <sup>2</sup> ) Optional 550 sheets x 2 cassettes (80g/m <sup>2</sup> ) 550 sheets x 1 cassette for imageRUNNER 2520 / 2520i only
	Paper Deck	None
	Total Capacity	2,300 sheets. (2,000 sheets for the imageRUNNER 2520i / 2520) Canon Custom Processor, 400MHz
	CPU	512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
	Memory	None
	Hard Disk Drive	None
	Interface	Ethernet (100Base-TX / 10Base-T), USB Host1 / F.2.0 x 1 port, USB Device 1.0 x 1 port
	Power Supply	220-240V AC, 50/60Hz, 4.2A (45 / 35ppm model), 220-240V AC, 50/60Hz, 3.3A (30 / 25 / 20ppm model)
	Max. Power Consumption	1.827kW (45 / 35ppm model), 1.345kW (30 / 25ppm), 1.542kW (20ppm model)
	Dimensions (W x D x H)	imageRUNNER 2545i / 2545 / 2535i / 2535: 565 x 680 x 806mm (with the platen cover), 565 x 689 x 907mm (with the DADF) imageRUNNER 2530i / 2530 / 2525i / 2525: 565 x 680 x 806mm (with the platen cover), 565 x 689 x 896mm (with the DADF) imageRUNNER 2520i / 2520: 565 x 680 x 681mm (with the platen cover), 565 x 689 x 771mm (with the DADF)
	Weight	imageRUNNER 2545i / 2535i: Approx. 78.4kg, imageRUNNER 2545 / 2535: Approx. 70.5kg, imageRUNNER 2530i / 2525i: Approx. 77.5kg, imageRUNNER 2530 / 2525: Approx. 68.0kg, imageRUNNER 2520i: Approx. 56.0kg, imageRUNNER 2520: Approx. 50.5kg
<b>PRINT SPECIFICATION</b>		
	PDL	UFRII-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)
	Resolution	600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
	Memory	512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
	Hard Disk	None
	CPU	Canon Custom Processor, 400MHz
	Fonts	PS Fonts: Roman 136, PCL Fonts: Roman 93
	Supported OS	PCL: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Postscript level 3 emulation: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later) UFRII-LT: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later
	Interface	Ethernet (100Base-TX / 10Base-T)
	Network Protocol	TCP / IP (LPD / Port9100, HTTP), SMB, SNMPv1, WSD, IPv4 / IPv6 support
	Pull Scan	Network TWIN Driver (75 / 100 / 150 / 200 / 300dpi 8bit colour / 75-600dpi 1bit Black-and-White)
<b>SEND SPECIFICATION/ CLR SEND KIT-Y1</b>		
	(standard on i models, optional on non i models)	
	Scan Speed	45 / 34ipm (45 / 35ppm model), 25 / 13ipm (30 / 25 / 20ppm model)
	Scan Resolution	100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
	Destinations	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 300 x 300dpi
	Address Book	E-Mail / Internet FAX (SMTP), PC / Server (SMB,FTP), USB memory keys
	File Format	Local (Max. 500) TIFF, JPEG, PDF, High compression PDF, Searchable PDF (optional with Searchable PDF-C1)

<b>DADF-AA1 for imageRUNNER 2545/2535</b>		
	Paper Size	A3, A4, A4R, A5, A5R
	Paper Weight	Single sided original: 42 to 128g/m <sup>2</sup> , Double sided original: 50 to 128g/m <sup>2</sup>
	Max. Number of Originals	100 sheets (A4, A4R, A5, A5R: 80g/m <sup>2</sup> ), 50 sheets (A3: 80g/m <sup>2</sup> )
	Document Scanning Speed (max.)	45ipm (A4, 600 x 600dpi: BW)
	Copy Scan	45 / 34ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour)
	Dimensions (W x D x H)	565 x 540 x 137mm
	Weight	Approx. 7.9kg
<b>DADF-AB1 for imageRUNNER 2530/2525/2520</b>		
	Paper Size	A3, A4, A4R, A5, A5R
	Paper Weight	Single sided original: 37 to 128g/m <sup>2</sup> , Double sided original: 50 to 128g/m <sup>2</sup>
	Max. Number of Originals	50 sheets (A4, A4R, A5, A5R: 80g/m <sup>2</sup> ), 25 sheets (A3: 80g/m <sup>2</sup> )
	Document Scanning Speed (max.)	25ipm (A4, 600 x 600dpi: BW)
	Copy Scan	25 / 13ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour)
	Dimensions (W x D x H)	565 x 544 x 126mm
	Weight	Approx. 7.0kg
<b>CASSETTE UNIT-W1 for imageRUNNER 2520/i</b>		
	Type	Front-loading adjustable drawers
	Paper Size	A3, A4, A4R, A5R
	Custom Size	139.7 to 297mm x 182 to 432mm
	Paper Weight	64 to 90g/m <sup>2</sup>
	Paper Capacity	550 sheets (80g/m <sup>2</sup> ) x 1 cassette
	Dimensions (W x D x H)	565 x 680 x 97mm
	Weight	Approx. 12.8kg
<b>CST. FEEDING UNIT-AE1 for all models</b>		
	Type	2 Front-loading adjustable drawers
	Paper Size	A3, A4, A4R, A5R
	Custom Size	139.7 to 297mm x 182 to 432mm
	Paper Weight	64 to 90g/m <sup>2</sup>
	Paper Capacity	550 sheets (80g/m <sup>2</sup> ) x 2 cassettes
	Dimensions (W x D x H)	565 x 680 x 248mm
	Weight	Approx. 24.0kg
<b>INNER FINISHER-B1 for all models</b>		
	Number of Trays	One stack tray (Optional 2nd Tray: INNER FIN ADD. TRAY-B1)
	Tray Capacity	A4, A5, A5R: 1,000 sheets (or 125mm in height) A3, A4R: 500 sheets (or 62.5mm in height)
	Staple Position	Corner, Double
	Staple Capacity	A4: 50 sheets x 30 sets; A4R / A3: 30 sheets x 15 sets
	Dimensions (W x D x H)	416 x 554 x 350mm, 703 x 554 x 350mm (with output tray extended)
	Weight	Approx. 12.5kg
<b>INNER 2-WAY TRAY-G1 for all models</b>		
	Number of Trays	2 stack tray
	Tray Capacity	A4: 250 sheets, A3: 100 sheets
	Tray A	A4: 100 sheets, A3: 50 sheets
	Tray B	426 x 413 x 109mm
	Dimensions (W x D x H)	Approx. 0.6kg
	Weight	
<b>OTHER ACCESSORIES</b>		
	Platen Cover Type P:	for imageRUNNER 2525/2530 without DADF
	Platen Cover Type Q:	for imageRUNNER 2535/2545 without DADF
	Stamp Ink Cartridge-C1	
	Stamp Unit-B	
	ADF Access Handle-A1	
	PCL Printer Kit-AF1:	Supports PCL5e and PCL6 printing for non-i Models
	PS Printer Kit-AF1:	Supports PostScript Level 3 Emulation printing.
	Barcode Printing Kit-B1:	Provides Barcode printing capability using Jet Caps technology
	Super G3 Fax Board-AG1:	Add fax functionality
	FL Cassette-A11:	This spare 550-sheet tray for cassette '1' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i
	FL Cassette-AK1:	This spare 550-sheet tray for cassette '2' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i or for Cassette Feeding Unit-AE1 or Cassette Module-W1
	FL Cassette-AL1:	This spare 250-sheet tray for cassette '1' of imageRUNNER 2520 / 2520i
	allows you to swap paper sizes without changing the printer settings. Cassette Spacer-A1:	Adjusts the height for 250-sheet cassette when combined with optional Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520 / 2520i only.
	2 Way Unit-B1:	Enhances the double-sided print productivity up to 100% Reversal Pass Unit (2-Way Unit) option for imageRUNNER 2520 / 2520i / 2525 / 2530.
	Staple-J1:	Staples for Inner Finisher-B1. Document Tray-J1: Handy tray that attaches to the side of the device.
	Power Supply Unit-U1.	
	Card Reader Attachment-D3:	Attachment kit for Card Reader-F1.
	Canon Card Reader-F1:	Physical card access system that limits system access to authorised users.
	USB Application 3-Port Interface Kit-A1:	3-Port USB interface kit for USB memory.
	CCV1 I/F Cable-A1:	Interface Kit for Coin-Vender.
	C-EXV33 TONER BK:	Toner for imageRUNNER 2520 / 2520i / 2525 / 2525i / 2530 / 2530i.
	C-EXV32 TONER BK:	Toner for imageRUNNER 2535 / 2535i / 2545 / 2545i
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.		



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English Edition 0163W635  
01/12/v1  
© Canon Europa N.V., 2012

Canon (UK) Ltd  
Woodhatch  
Reigate  
Surrey  
RH2 8BF  
Tel.: 01737 220000  
Fax: 01737 220022  
canon.co.uk

Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Tel.: 01 2052400  
Fax: 01 2052525  
canon.ie